# Yealink

# SIP-T48U

# A Revolutionary SIP Phone with a 7-inch Touch Screen

Yealink presents a dynamic business communication solution to executives and professionals with the new SIP-T48U IP phone. The phone employs an appealing large touch screen that makes the switch between pages and applications swift, easy and convenient. United Yealink Optima HD Voice technology and wideband codec of Opus, the T48U awards you the superb audio quality and crystal-clear voice communications. Moreover, the T48U puts dual USB ports in a phone that makes Bluetooth, Wi-Fi, USB headset and USB recording come true, and you can use any two of them freely according to your needs. The Yealink new T4U series offers the same elegant appearance as the T4 line, but with improvements for greater interoperability and better collaboration.











Opus Codec



7-inch Touch Screen

Optima HD Voice

Ports

Acoustic

Shield

Unified Firmware

Expansion Module

# Key Features and Benefits

# Easy Customization and High Expansibility

The SIP-T48U has a seven-inch, 800 x 480-pixel, backlit- color touch screen, which enables a rich visual presentation and easy navigation. Accompanied by two USB ports, the T48U is your right-hand man in the office that makes Bluetooth, Wi-Fi, USB headset and USB recording possible, and you can use any two of them freely according to your needs to enrich phone features. Meanwhile, the phone not only has 29 one-touch DSS keys that can be easily programmed to various features, but also can connect up to three expansion modules, for up to 180 additional buttons with a screen-based LCD display and LED system.

# HD Audio

Yealink Optima HD Voice technology combines cutting-edge hardware and software with wideband technology for maximum acoustic performance. Being a totally open, highly versatile audio codec, Opus, is designed to perform a higher HD audio quality than other wideband codecs in a high network bandwidth; However, if your current network quality is poor, Opus can provide you with a better audio quality than other narrowband codecs. And its hearing aid compatible (HAC) handset helps the person who is with hearing loss to hear the voice more clearly.

# Efficient Installation and Provisioning

Yealink T4U series supports efficient provisioning and effortless mass deployment with Yealink's Redirection and Provisioning Service (RPS) and Boot mechanism to help you realize the Zero Touch Provisioning without any complex manual settings, which makes the T4U series simple to deploy, easy to maintain and upgrade. Furthermore, a unified firmware and auto-p template that applies to all T4U phone models, saves even more time and costs for businesses, as well as simplifies the management and maintenance.

# Secure Transport and Interoperability

Yealink T4U series uses SIP over Transport Layer Security (TLS/SSL), which is the latest network security technology. It's also compatible with leading soft switch suppliers, such as 3CX, Broadsoft Broadworks. Moreover, it is carried with dual fimrware images that gives you a enterprise-level protection to avoid bricking your system once upgrade failed.

- 7" 800 x 480-pixel color touch screen with backlight
- Opus codec support
- Dual USB ports
- Dual firmware images
- T4U Auto-P template unified
- T4U firmware unified
- Up to 16 SIP accounts
- Dual-port Gigabit Ethernet
- PoE support
- Paperless label design
- Headset, EHS support
- Wi-Fi via WF40/WF50
- Bluetooth via BT40/BT41
- USB recording
- Supports color-screen expansion modules
- Stand with two adjustable angles
- Wall mountable

# Yealink

# Audio Features

- > HD voice: HD handset, HD speaker
- > Hearing aid compatible (HAC) handset
- > Acoustic Shield
- > Smart Noise Filtering
- Codecs: AMR-WB (optional), AMR-NB (optional),
  Opus, G.722, G.711(A/µ), G.723.1, G.729AB, G.726,
  iLBC
- > DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- > Full-duplex hands-free speakerphone with AEC
- > VAD, CNG, AEC, PLC, AJB, AGC

# Phone Features

- > 16 VoIP accounts
- > Call hold, mute, DND
- > One-touch speed dial, hotline
- > Call forward, call waiting, call transfer
- > Group listening
- > Emergency call
- > Redial, call return, auto answer
- > 10-way conferencing
- > Direct IP call without SIP proxy
- > Ring tone selection/import/delete
- > Set date time manually or automatically
- > Dial plan, XML Browser, action URL/URI
- > RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)> USB port (2.0 compliant) for:
  - Bluetooth earphone through BT40/BT41
  - Contact synchronization through BT40/BT41
  - Simultaneous connection of one headset and one mobile phone through BT40/BT41
  - Wi-Fi through WF40/WF50
  - USB call recording through USB flash drive
  - USB headset
  - Expansion Module EXP43
  - Wireless Headset Adapter EHS40
- > USB/Bluetooth connectivity to Yealink CP900/CP700 speakerphone, USB connectivity to Yealink UH36 headset:
  - Basic functions: Answer / end, call mute
  - Enhanced function: audio optimization, redial, call hold, volume synchronization, multiple calls control
- > Enhanced DSS key

# Directory

- > Local phonebook up to 1000 entries
- > Black list

Learn More

- > XML/LDAP remote phonebook
- > Smart dialing
- > Phonebook search/import/export
- > Call history: dialed/received/missed/forwarded

YEALINK NETWORK TECHNOLOGY CO., LTD.

# **IP-PBX** Features

- > Busy Lamp Field (BLF)
- > Bridged Line Apperance (BLA)
- > Anonymous call, anonymous call rejection
- > Hot-desking, voice mail
- > Flexible seating
- > Executive and Assistant
- > Call park, call pickup
- > Centralized call recording, call recording
- > Visual voice mail

# Display and Indicator

- > 7" 800 x 480-pixel color touch screen with backlight
- > 24 bit depth color
- > LED for call and message waiting indication
- > Wallpaper
- > Intuitive user interface with icons and soft keys
- > Multilingual user interface
- > Caller ID with name, number and photo
- > Screensaver
- > Power saving

#### Feature keys

- > 29 one-touch DSS keys
- > 7 features keys: message, headset, hold, mute, transfer, redial, hands-free speakerphone
- > 6 navigation keys
- > Volume control keys
- > Illuminated mute key
- > Illuminated headset key
- > Illuminated hands-free speakerphone key

#### Interface

- > Dual-port Gigabit Ethernet
- > 2 x USB port (2.0 compliant)
- > 1 x RJ9 (4P4C) handset port
- > 1 x RJ9 (4P4C) headset port

#### Other Physical Features

- > Color: Classic Grey
- > Wall mountable (optional)
- External Yealink AC adapter (optional):
  AC 100~240V input and DC 5V/2A output
- > USB output currency: 5V === 1A
- > Power consumption (PSU): 1.8-3.8W
- > Power consumption (PoE): 2.3-4.7W
- > Dimension (W\*D\*H\*T): 266mm\*226mm\*185mm\*54mm

Wi-Fi/Blueto USB Donal

Email: sales@yealink.com

> Operating humidity: 10~95%

ľ

Internet DC5V

0

To find out how Yealink solutions can help your organization, visit us at www.yealink.com or mail to sales@yealink.com

> Operating temperature: -10~50°C (+14~122°F)



#### Management

- > Configuration: browser/phone/auto-provision
- > Auto provision via FTP/TFTP/HTTP/HTTPS for
- mass deploy
- > Auto-provision with PnP
- > Zero-sp-touch, TR-069
- > Phone lock for personal privacy protection

> Proxy mode and peer-to-peer SIP link mode

> Time and date synchronization using SNTP

> QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP

- > Reset to factory, reboot
- > Package tracing export, system log

#### Network and Security

- > SIP v1 (RFC2543), v2 (RFC3261)
- > Call server redundancy supported
- > NAT traversal: STUN mode

> IP assignment: static/DHCP

> UDP/TCP/DNS-SRV(RFC 3263)

> Transport Layer Security (TLS)

> AES encryption for configuration file

> HTTPS certificate manager

> Digest authentication

> OpenVPN, IEEE802.1X

> LLDP/CDP/DHCP VLAN

- Yealink SIP-T48U IP phone

- Handset with handset cord

- Power Adapter (Optional)

- Wall Mount Bracket (Optional)

> Giftbox size: 324mm\*263mm\*128mm

> Carton Meas: 660mm\*338mm\*273mm

CE FC S REACH ISO 9001 💩 실

👎 broadsoft 3CX ⊆Genesys

Asterisk<sup>®</sup> ompatible

- Ethernet Cable (2m CAT5E UTP Cable)

Package Features

- Stand

> Package content:

- Quick Start Guide

> Qty/CTN: 5 PCS

> N.W/CTN: 7.9 kg

> G.W/CTN: 8.4 kg

Compliance

metaswitch

6

> HTTP/HTTPS web server

> SRTP for voice

> IPv6

> ICF



# About Yealink

Yealink is a global leading provider of enterprise communication and collaboration solutions, offering video conferencing service to worldwide enterprises. Focusing on research and development, Yealink also insists on innovation and creation. With the outstanding technical patents of cloud computing, audio, video and image processing technology, Yealink has built up a panoramic collaboration solution of audio and video conferencing by merging its cloud services with a series of endpoints products. As one of the best providers in more than 140 countries and regions including the US, the UK and Australia, Yealink ranks No.1 in the global market share of SIP phone shipments.

# Copyright

### Copyright © 2020 YEALINK(XIAMEN) NETWORK TECHNOLOGY CO., LTD.

Copyright © 2020 Yealink(Xiamen) Network Technology CO., LTD. All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Yealink(Xiamen) Network Technology CO., LTD.

### **Technical Support**

Visit Yealink WIKI (http://support.yealink.com/) for firmware downloads, product documents, FAQ, and more. For better service, we sincerely recommend you to use Yealink Ticketing system (https://ticket.yealink.com) to submit all your technical issues.



YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD. Web: www.yealink.com Addr: No.1 Ling-Xia North Road, High Tech Park, Huli District, Xiamen, Fujian, P.R. China Copyright©2020 Yealink Inc. All right reserved.